Airsonic (Advanced) Streamingserver

Ich nutze die Stand-alone-WAR.

> https://airsonic.github.io/docs/install/war-standalone/
>
> https://github.com/airsonic-advanced/airsonic-advanced/releases

Installation

Java JRE

Wie auch Subsonic ist Airsonic in Java geschrieben. Daher wird für den Betrieb das Java Runtime Environment in der Version 8 benötigt:

```
# aptitude install openjdk-8-jre
```

Für Airsonic Advanced wird Java 11 benötigt:

```
# aptitude install openjdk-11-jre
```

Falls bereits eine andere Java-Version installiert worden ist, kann über den folgenden Befehl Java 8 zum Systemstandard gemacht werden.

```
# update-alternatives --config java
```

Um zu erfahren, welche Java-Version Systemstandard ist, kann folgender Aufruf getätigt werden:

```
# java -version
openjdk version "1.8.0_292"
OpenJDK Runtime Environment (build 1.8.0_292-8u292-b10-0ubuntu1~20.04-b10)
OpenJDK 64-Bit Server VM (build 25.292-b10, mixed mode)
```

Optionale Tools

Optional können noch folgende Tools zur Bearbeitung der Musiksammlung installiert werden:

```
aptitude install id3 id3v2 eyed3
```

Das System vorbereiten

Umlegen des Arbeitsverzeichnises auf eine andere Platte:

```
# mkdir -p /srv/airsonic
```

```
# cd /var
# ln -s  /srv/airsonic airsonic
```

Nun legen wir das Dienstkonto an:

```
# useradd -M -r -s /usr/sbin/nologin -d /var/airsonic airsonic
# chown -R airsonic:airsonic /srv/airsonic
```

Die Anwendung als Dienst implementieren

Bei Airsonic:

```
# wget
https://raw.githubusercontent.com/airsonic/airsonic/master/contrib/airsonic.
service -O /etc/systemd/system/airsonic.service
# wget
https://raw.githubusercontent.com/airsonic/airsonic/master/contrib/airsonic-
systemd-env -O /etc/default/airsonic
# wget -c
https://github.com/airsonic/airsonic/releases/download/v10.6.2/airsonic.war
# cp airsonic.war /srv/airsonic
# systemctl daemon-reload
# systemctl start airsonic.service
# systemctl enable airsonic.service
```

Bei Airsonic Advanced:

```
# wget
https://raw.githubusercontent.com/airsonic-advanced/airsonic-advanced/master
/contrib/airsonic.service -O /etc/systemd/system/airsonic.service
# wget
https://raw.githubusercontent.com/airsonic/airsonic/master/contrib/airsonic-
systemd-env -O /etc/default/airsonic
# wget -c
https://github.com/airsonic-advanced/airsonic-advanced/releases/download/11.
0.0-SNAPSHOT.20211007145752/airsonic.war
# cp airsonic.war /srv/airsonic
# systemctl daemon-reload
# systemctl start airsonic.service
# systemctl enable airsonic.service
```

Innerhalb der airsonic.service muss der Pfad für `EnvironmentFile` an die Gegebenheiten in Ubuntu angepasst werden.

/etc/systemd/system/airsonic.service

```
[Unit]
Description=Airsonic Media Server
After=remote-fs.target network.target
```

```
AssertPathExists=/var/airsonic

[Service]
Type=simple
Environment="JAVA_JAR=/var/airsonic/airsonic.war"
Environment="JAVA_OPTS=-Xmx700m"
Environment="AIRSONIC_HOME=/var/airsonic"
Environment="PORT=8080"
Environment="CONTEXT_PATH=/airsonic"
Environment="JAVA_ARGS="
EnvironmentFile=-/etc/default/airsonic
ExecStart=/usr/bin/java \
          $JAVA_OPTS \
          -Dairsonic.home=${AIRSONIC_HOME} \
          -Dserver.servlet.context-path=${CONTEXT_PATH} \
          -Dserver.port=${PORT} \
          -jar ${JAVA_JAR} $JAVA_ARGS
User=airsonic
Group=airsonic

# See
https://www.freedesktop.org/software/systemd/man/systemd.exec.html
# for details
DevicePolicy=closed
NoNewPrivileges=yes
PrivateDevices=yes
PrivateTmp=yes
PrivateUsers=yes
ProtectControlGroups=yes
ProtectKernelModules=yes
ProtectKernelTunables=yes
RestrictAddressFamilies=AF_UNIX AF_INET AF_INET6
RestrictNamespaces=yes
RestrictRealtime=yes
SystemCallFilter=~@clock @debug @module @mount @obsolete @privileged
@reboot @setuid @swap
ReadWritePaths=/var/airsonic

# You can change the following line to `strict` instead of `full`
# if you don't want airsonic to be able to
# write anything on your filesystem outside of AIRSONIC_HOME.
ProtectSystem=full

# You can uncomment the following line if you don't have any media
# in /home/…. This will prevent airsonic from ever reading/writing
anything there.
#ProtectHome=true

# You can uncomment the following line if you're not using the OpenJDK.
# This will prevent processes from having a memory zone that is both
writeable
```

```
# and executeable, making hacker's lifes a bit harder.
#MemoryDenyWriteExecute=yes


[Install]
WantedBy=multi-user.target
```

From:
https://wikinet.webby.hetzel-netz.de/ - **Sebastians IT-Wiki**

Permanent link:
https://wikinet.webby.hetzel-netz.de/ubuntu:airsonic?rev=1633863285

Last update: **2021/10/10 10:54**